

AMERICANA®

FP410 / FP420 Series Ceiling Fans



| Short Fan Assembly - FP410** | |
|--|--------|
| Overall Height (w/o Light Kit) | 25" |
| Blade Sweep | * |
| Base Diameter | 16¾" |
| Mounting Diameter (3-hole; centerline) | 13" |
| Weight: (w/o Light Kit) | 32 lbs |

| Long Fan Assembly - FP420** | |
|--|--------|
| Overall Height (w/o Light Kit) | 39" |
| Blade Sweep | * |
| Base Diameter | 16¾" |
| Mounting Diameter (3-hole; centerline) | 13" |
| Weight: (w/o Light Kit) | 41 lbs |

*Blade sweep varies depending on blade selection, see chart on page 79

| Available Finishes | |
|--------------------|---------------|
| AB | Antique brass |
| BL | Black |

| Ordering Information | |
|----------------------|---|
| Catalog No. | Description |
| FP410** | Short fan assembly |
| FP420** | Long fan assembly |
| FP1018 | Reversible oak/walnut blade set (sold separately) |

INSTALLATION REQUIREMENTS:

Requires 3/4" plywood wall backing, able to support at least 100 lbs. Fan base is secured to 3/4" plywood backing using three 5/16" lag bolts. Ceiling backing to be supplied by owner or contractor.

ELECTRICAL REQUIREMENTS:

Surface mounted electrical junction box centered in mounting location with a grounded electrical supply line of 120 volts AC, 60 Hz, 15 amp circuit.

MOTOR SPECS:

FK2100 motor is designed for optimal performance with this fan. 220 VAC, 50 Hz export version available (antique brass only). Reversing switch and 3-speed pull-chain included.

BLADES:

A variety of 4- and 5-blade sets are available. 5-blade sets are available in palm, bamboo, wood and composite materials. 4-blade sets are made of wood and require the use of BH20 series blade holders (not included). 4-blade sets will increase speed and airflow. See our catalog or visit www.fanimation.com for blade options.

Note: Fan speeds will vary according to blade set—material, shape and size of blade. In general, smaller blades will turn faster than bigger ones and narrower blades will turn faster than wider ones.

CONTROL OPTIONS:

Optional CW1, CW1SW and CW2 wall controls available—sold separately. Optional TR20 remote control available with use of optional SW50 switch cap receiver—all sold separately. Instructions are provided with each control.

LIGHTING OPTIONS:

Optional lighting fitters and light kits are available—see our catalog or visit www.fanimation.com.

LOCATION USAGE:

FP410AB/FP420AB is rated for dry locations only. FP410BL/FP420BL is rated for dry and damp locations.