
PALISADE®



FP240**-220 Ceiling Fan Assembly



Available Finishes				
AB	Antique brass			
PW	Pewter			
RS	Rust (Damp)			
ОВ	Oil-rubbed bronze (Damp)			
Component Weights				
Motor Assembly Unit (2)		14 lbs		
Horizontal Tube Assembly		5 lbs		
Blade Set (8)†		3-5 lbs		
Extension Pole†		1 lb/ft		
[†] Sold Separately				

Distance from Ceiling to Bottom of Blades	Α
*24" Pole w/18" Palm Blades	51″
30" Pole w/22" Palm Blades	61″
36" Pole w/22" Palm Blades	67″
48" Pole w/22" Palm Blades	79″
60" Pole w/22" Palm Blades	91″
72" Pole w/22" Palm Blades	103″

^{* 24&}quot; extension pole may be used with 18" blades only

^{*} Can be mounted on a sloped ceiling up to 45°

TUV/GS Efficiency Info (220V)					
Fan Speed	Max RPM	Amps	Watts		
High	60	0.57	117		
Med	40	0.50	89		
Low	20	0.42	76		

INSTALLATION REQUIREMENTS:

Fan uses a ball and bracket hanging system; must be secured to a structural member, such as a ceiling joist, capable of withstanding a load of at least 100 lbs. A $^{3}I_{8}$ " x 5" long lag bolt passes through loop in ceiling support cable, hanger bracket plate, and into wood structural member above.

ELECTRICAL REQUIREMENTS:

Requires a grounded electrical supply line of 220~240 volts AC, 50 Hz, 5 amp circuit.

MOTOR SPECS:

Two FK2100-220 motors are designed for optimal performance with this fan.

BLADES:

A variety of palm, bamboo, and wood blades are available—sold separately; see our catalog or visit www.fanimation.com.

CONTROL OPTIONS:

C3-220 3-speed wall control is included. Optional C6-220 remote control is available for light kit installed—sold separately. Instructions are provided with each control.

LIGHTING OPTIONS:

Optional lighting fitters and light kits are available. See our catalog or visit www.fanimation.com for available lighting options.

EXTENSION POLE:

An extension pole coupler is available for installations requiring an extension pole longer than 72". Fan can be mounted on a sloped ceiling up to 30°. Optional sloped ceiling ball kit (SCB1–52) is available for slope angles greater than 30° and up to 52°.

ACCESSORY OPTIONS:

Various optional accessories are available; see our catalog or visit www.fanimation.com.

LOCATION USE:

Fan is dry location rated only. Damp location rated with use of rust finish fan assembly and woven bamboo or all-weather composite blades.