



	Α	В
Fan w/4.5" downrod	14.51"	13.01"
Fan w/12" downrod	22.01"	20.51"
Fan w/18" downrod	28.01"	26.51"
Fan w/24" downrod	34.01"	32.51"
Fan w/36" downrod	46.01"	44.51"
Fan w/48" downrod	58.01"	56.51"
Fan w/60" downrod	70.01"	68.51"
Fan w/72" downrod	82.01"	80.51"

Available Finishes			
Fan /	Housing Assembly	Blades - Traditional	
OB	Oil-rubbed Bronze	Walnut / Cherry	
WH	White	White / White Oak	

CFM / Watts

89

91

123

Estimated Yearly

Energy Cost (\$)

14

Amps

0.65

0.62

0.42

Watts

69

64

Ceiling Fan

Efficiency

(CFM/W)

Airflow / Energy Efficiency Info (120V)

CFM

6185

5789

3457

Energy Guide FTC

Max RPM

83

79

Total Air Delivery

4906

(CFM_{ave})

Fan Speed

High

Med

Low

Power

(W_{ave})

INSTALLATION REQUIREMENTS:

Fan must be attached to a securely anchored electrical junction box capable of withstanding a load of at least 35 lbs.

ELECTRICAL REQUIREMENTS:

Requires a grounded electrical supply line of 120 volts AC, 60 Hz, 15 amp circuit.

MOTOR SPECS:

212 x 35 AC motor is designed for optimal performance with this. fan.

BLADES:

A set of five 31" reversible plywood blades is included.

CONTROL OPTIONS:

Optional CW5, WC1WH, WC2WH, WR500WH, WR501WH and CWRL4 wall controls are available—sold separately.

Optional BTCR9, CRL4WH and CR500 remote controls with receiver unit and BTR9 receiver unit and WFR 50 WiFi receiver unit are available—sold separately. Instructions are provided with each control.

LIGHTING OPTIONS:

Optional lighting fitters and light kits are available. See our catalog or visit www.fanimation.com for available lighting options.

DOWNROD OPTIONS:

Fan comes with 1" dia. x 4.5" long downrod (DR1-45). Optional downrods available in 12", 18", 24", 36", 48", 60", and 72" lengths. A downrod coupler is available for installations requiring a downrod longer than 72". Fan must use 18" or longer downrod, and can be mounted on a sloped ceiling up to 19°. Optional close-to-ceiling kit is available as well—sold separately. Optional sloped ceiling kits (SCK1-52) are available for up to 42°. Call your local dealer for more information.

LOCATION USE:

Fan is rated for dry locations only.